


7603

Acrylic Transfer Tape



Liner: 2 mil Clear PET Film

Adhesive: Acrylic (1637)

Applications

 Ideal for bonding to vinyl products such as flooring, wall covering, synthetic leather, and banner stock

Features Benefits

Acrylic Adhesive	Moderate tack which develops a stronger bond	
	over time	
	Plasticizer-resistant	
	 Offers short-term repositionability 	
PET Film Liner	 Improved die-cutting and kiss cutting 	
	 Smooth, clean removal 	

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesive Thickness	3.0 mils	0.076 mm	PSTC 133
Liner Thickness	2.0 mils	0.051 mm	PSTC 133
Adhesion to Steel	50 oz/in	5.47 N/cm	PSTC 101 Mod - 1 mil PET
Adhesion to Steel	150 oz/in	16.41 N/cm	PSTC 101 Mod - 4 mil Alu Foil
Shear Strength (at 72 °F)	168 Hours		PSTC 107 Mod
Laminating Temperature	68 to 100 °F	20 to 38 °C	
Service Temperature	-30 to 220 °F	-34 to 104 °C	

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

Standard Shelf Life: 12 months from date of shipment

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

