


POLYKEN® 3426B

Flexible Film Tape



Backing:	4 mil PE Film
Adhesive:	Medical-grade Rubber (M117)
Liner:	60lb bleached super-calendered kraft, silicone coated on both sides

Applications

- Mounting and laminating electronic component
- Medical device component
- Patient monitoring
- Medical device assembly
- Sensor components
- Pulse oximetry

Features

- PE Film Backing
- Rubber Adhesive
- 60lb Release Liner

Benefits

- Flexible and conformable for patient comfort
- High tack, bonds well to various materials
- Easy to die-cut and convert

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness w/liner	9.3 mils	0.236 mm	PSTC 133
Adhesive Thickness	1.8 mils	0.046 mm	PSTC 133
Carrier Thickness	4.0 mils	0.102 mm	PSTC 133
Liner Thickness	3.5 mils	0.089 mm	PSTC 133
Adhesion to Steel	140 oz/in	15.32 N/cm	PSTC 101 Mod

Product Safety

The base adhesives in this medical product have been tested in accordance with ISO 10993 and found to be non-irritating and non-cytotoxic.

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

