


POLYKEN® 3428R

Single-Coated Film Tape



Liner:	80lb bleached, silicone release treated on both sides
Backing/Carrier:	1.0 mil polyurethane film
Adhesive:	Non-irritating medical-grade acrylic (M159)

Applications

- Mounting and laminating electronic components
- Medical device component
- Patient monitoring
- Medical device assembly
- Sensor components

Features

- Polyurethane Film Carrier
- Non-Irritating Acrylic Adhesive
- 80lb Release Liner

Benefits

- High breathability and conformability for extended wear and maximum patient comfort
- Excellent adhesion to skin and other surfaces
- Suitable for long-term wear
- Easy to use and convert

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness w/liner	7.3 mils	0.185 mm	PSTC 133
Adhesive Thickness	2.1 mils	0.053 mm	PSTC 133
Carrier Thickness	1.0 mils	0.025 mm	PSTC 133
Liner Thickness	4.2 mils	0.107 mm	PSTC 133
Adhesion to Steel	60 oz/in	6.56 N/cm	PSTC 101 Mod

Product Safety

The base adhesives in this medical product have been tested in accordance with ISO 10993 and found to be non-cytotoxic, non-sensitizing, and non-irritating.

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.