

TECHNICAL BULLETIN

FILM SUPPORTED TAPE

PRODUCT:	3175M Double-Coated Polyester Film			
PRIMARY USE:	<p>3175M is designed to incorporate the following features: The exposed side adhesive is a general purpose rubber-based adhesive designed for bonding to a wide variety of polyurethane and polyethylene foams, felt, rubber, sponge, cork, abrasive materials and gasket materials.</p> <p>The liner side adhesive is a different rubber-based adhesive that bonds well to most substrates at room temperature. This adhesive exhibits high initial tack and high peel strength.</p>			
LINER:	60# white poly-coated Kraft.			
TYPICAL PHYSICAL PROPERTIES:	Thickness	Carrier	0.5 mils	
		Adhesive Exposed Side (nominal)	1.4 mils	
		Adhesive Liner Side (nominal)	1.3 mils	
		Liner (nominal)	3.5 mils	
	Peel Adhesion	PSTC #101 Method C; backed with 1 mil polyester <i>24 Hour Dwell:</i>		
		Exposed Side		145 oz/inch
		Liner Side		125 oz/inch
		PSTC #101 Method C; backed with 2 mil dead soft aluminum foil <i>24 Hour Dwell:</i>		
		Exposed Side		230 oz/inch
		Liner Side		220 oz/inch
	Shear Adhesion	PSTC #107; Procedure A, Modified, 1000 gm/sq. inch @ 72° F. <i>No Dwell:</i>		
		Exposed Side		24 Hours
		Liner Side		24 Hours
PRODUCT FEATURES:	<ul style="list-style-type: none"> Excellent bond to urethane foams. Die cuts cleanly. Available on 60# poly-coated lay-flat liner. 54" & 60" widths available. 			

ADCHEM CORPORATION

1852 Old Country Road
Riverhead, NY 11901
P: 631-727-6000

adchem.com



Data presented are typical properties taken from a limited number of production runs and should not be used for specification purposes. Adchem Corporation makes no warranty, expressed or implied, and specifically disclaims and disavows any implied warranty of merchantability and of fitness for a particular purpose. Accordingly, all Adchem products are sold with the understanding that purchasers will be solely responsible for determining the suitability of the materials for any purpose.

TECHNICAL BULLETIN

3175M Double-Coated Polyester Film

SERVICE TEMPERATURE:	30°F to150°F NOTE: This information is provided as a means to help characterize the adhesive's temperature resistance. Note that this data is based on limited testing and under no load. The practical service temperature of this or any adhesive system is dependent on many variables including the substrates being bonded, environmental conditions, and the loading and method of application. The purchaser is responsible for determining the suitability of this or any product for their particular purpose and process. The recommended application temperature is 68°F to 100°F.
NOTES:	The use of heat and pressure will help to increase the initial bond of the product to the substrate. Testing is recommended prior to laminating to any material that contains migrating plasticizers.
RELATED ADCHEM PRODUCTS:	Other double-coated rubber products include: 2237M – Exposed side adhesive of 3175 at 1.75 mils each side. 5008B – Aggressive heat resistant solvent-based system. 262C – Crepe paper carrier for conformability and tearability. 262T – Tissue carrier for conformability and tearability.
SHELF LIFE:	One year from date of shipment when stored under cool, dry conditions.

Rev. 08.07.12

ADCHEM CORPORATION

1852 Old Country Road

Riverhead, NY 11901

P: 631-727-6000

adchem.com