


2237M Double-Coated PET Film Tape



Liner:74# Polycoated KraftLiner Side Adhesive:Rubber (1917)Backing/Carrier:0.5 mil PET FilmAir Side Adhesive:Rubber (1917)

Applications

- Bonding and laminating to a variety of plastics, metals, and papers
- Laminating to cork, felt, abrasives, and more
- Splicing and general purpose holding

Features	Benefits
Rubber Adhesive	 Excellent quick stick to difficult surfaces
	 Moderate shear strength
Polyester Film Carrier	 Support for aid in processing and application
	Conformable
• 74# Polycoated Kraft Liner	 Conformable and good dimensional stability

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Overall Thickness (w/liner)	9.5 mils	0.241 mm	PSTC 133
Adhesive Thickness (Air Side)	1.75 mils	0.044 mm	PSTC 133
Carrier Thickness	0.5 mils	0.013 mm	PSTC 133
Adhesive Thickness (Liner Side)	1.75 mils	0.044 mm	PSTC 133
Liner Thickness	5.5 mils	0.140 mm	PSTC 133
Adhesion to Steel (Air Side)	215 oz/in	23.52 N/cm	PSTC 101 Mod - 1 mil PET
Adhesion to Steel (Liner Side)	225 oz/in	24.62 N/cm	PSTC 101 Mod - 1 mil PET
Adhesion to Steel (Air Side)	285 oz/in	31.18 N/cm	PSTC 101 Mod - 2 mil Alu Foil
Adhesion to Steel (Liner Side)	320 oz/in	35.01 N/cm	PSTC 101 Mod - 2 mil Alu Foil
Shear Strength	7 Days		PSTC 107 Mod
Laminating Temperature	68 to 100 °F	20 to 38 °C	
Service Temperature	30 to 150 °F	-1 to 66 °C	

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

Standard Shelf Life: 12 months from date of shipment

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryglobal.com