


3615A Double-Coated Tape



Liner: 76lb white polycoated kraft liner

Liner Side Adhesive: Acrylic (1618)

Backing/Carrier: 0.5 mil polyester film

Air Side Adhesive: Acrylic (1618)

Applications

 General purpose laminating for paper, felt, foam and plastic

- Assembly and fastening of components
- General purpose splicing applications

Features Benefits

Polyester Film Carrier	 Support for aid in processing and application 	
	 Easily conforms to various surface types 	
 Acrylic Adhesive 	 High tack, medium peel adhesive 	
	 Bonds well to ABS, PC, LDPE, and HDPE 	
76lb Silicone Coated Kraft Liner	Easy to die cut and convert	

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness w/liner	8.8 mils	0.224 mm	PSTC 133
Adhesive Thickness (Air Side)	1.4 mils	0.036 mm	PSTC 133
Carrier Thickness	0.5 mils	0.013 mm	PSTC 133
Adhesive Thickness (Liner Side)	1.4 mils	0.036 mm	PSTC 133
Liner Thickness	5.5 mils	0.140 mm	PSTC 133
Adhesion to Steel (Air Side)	130 oz/in	14.22 N/cm	PSTC 101 Mod
Adhesion to Steel (Liner Side)	40 oz/in	4.38 N/cm	PSTC 101 Mod
Shear Strength	<24 Hours		
Laminating Temperature	50 to 150 °F	10 to 65 °C	
Service Temperature	-24 to 200 °F	-31 to 93 °C	

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

