


GTW-292

Double-Coated Foam Glazing Tape

4 mil Blue PP



Liner Side Adhesive: Acrylic (1636)				
Backing/Carrier:	1/16" 4lb Closed-Cell, Crosslinked White (or Black) PE Foam			
Air Side Adhesive:	Acrylic (1636)			
Specifications:	AAMA 810.1-16 for expanded cellular alazina tape			

Note: Same product is also available on **Black** color foam as **GTB-292**

Applications

Liner:

 Seal window glass onto wood, aluminum, or plastic frames

Eagturaa

Seals against air, moisture, light, and dust

		Benefits
t, and dust	•	Thermal insulating and sound deadening
aluminum, or	•	Provides cushioning to absorb vibration and shock

rediures	benemis
Acrylic Adhesive	Excellent quick stick
	 Moderate shear strength
	Good UV resistance
Foam Carrier	Conformable
	 Minimal moisture absorption
PE Film Liner	 Lends itself to die-cutting and kiss cuts

Typical Test Values

	71		
	Standard UOM	Metric UOM	Test Method
Overall Thickness (w/liner)	70.5 mils	1.791 mm	PSTC 133
Air-Side Adhesive Thickness	2.0 mils	0.051 mm	PSTC 133
Carrier Thickness	62.5 mils	1.588 mm	PSTC 133
Liner Side Adhesive Thickness	2.0 mils	0.051 mm	PSTC 133
Liner Thickness	4.0 mils	0.102 mm	PSTC 133
Adhesion to Steel (Air Side)	N/A*		PSTC 101 Mod
Shear Strength	>7 Days		PSTC 107 Mod
Laminating Temperature	68 to 100 °F	20 to 38 °C	
Service Temperature	-30 to 220 °F	-34 to 104 °C	

*Adhesive peel strength supercedes cohesive strength of the foam carrier.

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

Standard Shelf Life: 12 months from date of shipment

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryglobal.com