
POLYKEN[®] 3355H

Single-Coated Foam Tape



Backing:	1/32" white, crosslinked polyethylene foam
Adhesive:	Highly moisture-resistant, non- sensitizing medical grade acrylic (M110)
Liner:	96lb bleached polycoated kraft, silicone treated on one side

Applications

- Electrodes: ECG, EKG, TENS
- AED defibrillator pads

- Medical device mounting
- Transdermal delivery system

Features Benefits Polyethylene Foam Backing Soft and flexible for maximum patient comfort Conformable and easily adapts to medical • devices and body contours Acrylic Adhesive Aggressive adhesive designed for extended wear applications Removes cleanly without causing trauma Stable to EtO and gamma sterilization Highly resistant to perspiration-borne moisture 96lb Kraft Liner Easily die-cut into various shapes and sizes Dimensionally stable and moisture resistant

Typical Test Values

		Matria HOM	To at Math a d
	Standard UOM	Metric UOM	Test Method
Total Thickness w/liner	41.0 mils	1.041 mm	PSTC 133
Adhesive Thickness	3.0 mils	0.076 mm	PSTC 133
Carrier Thickness	31.2 mils	0.792 mm	PSTC 133
Liner Thickness	6.8 mils	0.173 mm	PSTC 133
Adhesion to Steel	80 oz/in	8.75 N/cm	PSTC 101 Mod
	Dreduce	t Cofot	

Product Safety

The base adhesives in this medical product have been tested in accordance with ISO 10993 and found to be non-cytotoxic, non-irritating, and non-sensitizing.

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the information and use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



101 Oakley Street Evansville, IN 47710 1-800-343-7875 Fax 1-800-328-4822 www.berryglobal.com