
## POLYKEN<sup>®</sup> 33M6H

### **Double-Coated Tape**



Liner:60lb semi-bleached kraft, silicone<br/>release coated on both sidesLiner Side Adhesive Acrylic (M123)Backing/Carrier:0.5 mil polyester film

Air Side Adhesive: Acrylic (M123)

#### Applications

- Polybag sealing
- Laminating paper, felt, sponge, rubber, foam, and plastic
- Gasket Assembly
- Mounting nameplates, decals, and plastic trim

# Features Benefits • Polyester Film Carrier • Support for aid in processing and application • Acrylic Adhesive • Excellent anchorage to foams and plastics • Acrylic Adhesive • Excellent performance over a wide temperature range • 60lb Semi-bleached Kraft Liner • Easy to die-cut and process

#### **Typical Test Values**

	i ypical i	est values	
	Standard UOM	Metric UOM	Test Method
Total Thickness w/liner	7.8 mils	0.198 mm	PSTC 133
Adhesive Thickness (Air Side)	1.9 mils	0.048 mm	PSTC 133
Adhesive Thickness (Liner Side)	1.9 mils	0.048 mm	PSTC 133
Carrier Thickness	0.5 mils	0.013 mm	PSTC 133
Liner Thickness	3.5 mils	0.089 mm	PSTC 133
Adhesion to Steel (Air Side)	90 oz/in	9.85 N/cm	PSTC 101 Mod
Adhesion to Steel (Liner Side)	100 oz/in	10.94 N/cm	PSTC 101 Mod
Shear Strength	>24 hours		PSTC 107
Application Temperature	50 to 150 °F	10 to 65 °C	
Maximum Continuous Use	200 °F	93 °C	
Intermittent Use	250 °F	121 °C	
	Produc	ct Safety	

The base adhesives in this medical product have been tested in accordance with ISO 10993 and found to be non-cytotoxic, non-sensitizing, and non-irritating.

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



101 Oakley Street Evansville, IN 47710 1-800-343-7875 Fax 1-800-328-4822 www.berryglobal.com