


3500B

Transfer Adhesive



Medical-grade acrylic (M160) Adhesive:

80lb white kraft liner, silicone release Liner:

treated on both sides with differential

release

Applications

Medical device attachment

Medical device assembly

Polybag closure

Features Benefits

Medical Grade Acrylic	 Good humidity and stress resistance 		
	Aggressive bond		
	 Adheres well to foams and plastics 		
	including PE, TPO, ABS, and PP		
80lb Release Liner	Easy liner removal		

Typical Test Values

	Standard UOM	Metric UOM	Test Method		
Total Thickness w/liner	6.5 mils	0.165 mm	PSTC 133		
Adhesive Thickness	2.0 mils	0.051 mm	PSTC 133		
Liner Thickness	4.5 mils	0.114 mm	PSTC 133		
Adhesion to Steel	100 oz/in	10.94 N/cm	PSTC 101 Mod		
Product Safety					

The base adhesives in this medical product have been tested in accordance with ISO 10993 and found to be noncytotoxic and non-irritating.

Shelf Life: 2 years from date of shipment

Recommended Storage Conditions: 50% Humidity, 70°F, out of direct sunlight

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

