
## POLYKEN<sup>®</sup> 3585A

**Backing:** 

## **Single-Coated Foam Tape**

1/16" white, crosslinked polyethylene foam



Adhesive:Highly Moisture-Resistant, Extended-wear<br/>Acrylic (M110)Liner:74lb bleached polycoated kraft, silicone<br/>treated on one side

Electrodes:	ECG.	EKG.	TENS	

• AED defibrillator pads

- Applications
  - Medical device mounting
  - Transdermal delivery system

Features	Benefits	
Polyethylene Foam Backing	<ul> <li>Soft and flexible for maximum patient comfort</li> <li>Conformable and easily adapts to medical</li> </ul>	
	devices and body contours	
Acrylic Adhesive	<ul> <li>Aggressive adhesive designed for extended wear applications</li> <li>Removes cleanly without causing trauma</li> </ul>	
	<ul> <li>Highly resistant to perspiration-borne moisture</li> </ul>	
74lb Kraft Liner	<ul><li>Easily die-cut into various shapes and sizes</li><li>Good dimensional stability and lay flat</li></ul>	

## **Typial Test Values**

	Standard UOM	Metric UOM	Test Method			
Total Thickness w/liner	70.1 mils	1.781 mm	PSTC 133			
Adhesive Thickness	2.0 mils	0.051 mm	PSTC 133			
Carrier Thickness	62.5 mils	1.588 mm	PSTC 133			
Liner Thickness	5.6 mils	0.142 mm	PSTC 133			
Adhesion to Steel	80 oz/in	8.75 N/cm	PSTC 101 Mod			
Product Safety						

The base adhesives in this medical product have been tested in accordance with ISO 10993 and found to be noncytotoxic, non-irritating, and non-sensitizing.

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



101 Oakley Street Evansville, IN 47710 1-800-343-7875 Fax 1-800-328-4822 www.berryglobal.com